

EASY REPLACEMENT VENT, 6"x16"

FOUNDATION • SUBFLOOR • SOFFIT • GARAGE



EZRvent FV100

3 easy installation steps:

1. Remove old screen, leaving old vent frame in place
2. Push EZRvent into old vent opening
3. Secure using one 2-1/2" screw on each end

- Easy to Install
- Higher Grade
- Retrofit
- New Construction

EZRvent FV100 is an easy to install replacement vent for 6" x 16" foundation, sub-floor, soffit and garage vents. Our FV100 is made of a durable UV protected plastic and heavy gauge galvanized, stainless, or copper screen that will last for years.

Installation is easy and saves labor time! Simply remove the old vent screen, push the new EZRvent in place, and install one 2-1/2" screw at each end of the vent. It's as easy as that!

Existing stucco and siding remains intact.

Although designed as a replacement / retrofit vent to keep the critters out, the EZRvent FV100 can be used in new construction for a higher grade finished look than standard new construction vents. With their unique picture frame shadow box styling and recessed screens, EZRvents are a perfect complement to vinyl clad windows and doors.

**FITS ROUGH OPENING
SIZE: 5" x 14"**

(4-1/2" x 13" MIN TO 6" x 14-1/2" MAX)



www.EZRvent.com • sales@EZRvent.com • 760-908-2369
5301 Los Robles, Suite 101 • Carlsbad CA 92008


See www.EZRvent.com for more information and installation videos.



Before: Old Rusted Out Vents



After: Installed EVRvent



PRODUCT FEATURES:

- Higher Grade Construction
- Higher Grade Look and Finish: picture frame shadow box frame with recessed screen
- One size covers a range of openings
- Easy and Quick install: Vents are pre drilled and countersunk
- No stucco or siding replacement required for installation
- Securely mounts with two internal surface screws
- 1/8" mesh screen offers added protection of keeping swarming bees out in addition to all the other critters. This option became so popular, that it is now our standard.
- Stainless Steel and Copper mesh options are available for the most demanding coastal applications
- Unique Patent Pending Design
- Made in USA

FV100 SPECIFICATIONS:

CONSTRUCTION:

- Frame Body: Durable UV stabilized polypropylene
- Screen Mesh:
 - -8: Light .017 Galvanized 1/8" Mesh – Special Order
 - -8H: Heavy .023 Galvanized 1/8" Mesh – Standard
 - -SS8H: Heavy .028 316 Stainless 1/8" Mesh – Special Order
 - -8HC: Heavy .028 Copper 1/8" Mesh – Special Order
- Frame Colors:
 - W: White - Standard
 - G: Cape Cod Gray – Special Order
 - S: Sand / Beige – Special Order
 - B: Brown / Bronze – Special Order
 - C: Custom Color (Primed & Painted) – Special Order



white



cape cod gray



sand / beige



brown / bronze

ROUGH OPENING 5" x 14":

- Min. 4.5" x 13" or 5" x 13" with trim tab modification
- Max. 6" x 14.5"

NET FREE VENTILATION:

- -8 = 35.6 sq in
- -8H = 28.9 sq in
- -SS8H = 28.9 sq in
- -8HC = 28.9 sq in



www.EZRvent.com • sales@EZRvent.com • 760-908-2369
5301 Los Robles, Suite 101 • Carlsbad CA 92008

See www.EZRvent.com for more information and installation videos.